


Resettable Combination Lock – 40000 Series Premier Lockers Operating & Programming Instructions

The resettable combination lock is durable and provides 4-digit user combination access as well as master key override for management.

Please read this entire page before use.



The lock features (4) number dials for setting a 4-digit user combination. When the lock is in the “closed position”, the arrow on the operation knob will be in the 9-o'clock position and a red indicator appears in a window above the operation knob. When the lock is in the (open position), the arrow on the operation knob will be in the 12-o'clock position and a green indicator appears in the window above the operation knob.

The factory preset combination is **0000**. Master key operation may be used at any time to open a lock.

UNLOCKING/OPENING THE LOCK:

1. If locked, turn the four (4) dials to the current 4-digit user combination code.
2. Turn the operation knob from the 9-o'clock closed position to the 12-o'clock open position, the color indicator will change from red to green.
3. Pull the operation knob to open the locker door.

Note: Turning the number dials in the open position will set a new code.

LOCKING/CLOSING THE LOCK:

1. Close the locker door.
2. Turn the operation knob from 12-o'clock to the 9-o'clock position, the color indicator will change from green to red. The lock CAM should be engaging, preventing the locker door from opening.
3. Scramble the four (4) dials to lock. The operation knob should not rotate away from the 9-o'clock position.

SETTING A NEW COMBINATION

Note: If the current code is unknown, use the Master Key Decode steps to determine the current code

1. Unlock the combination lock using the current 4-digit combination code. (See Unlocking/Opening steps). The lock needs to be in the opened position before a new code can be set.
2. With the lock in the open position, turn the dials to set a new combination.
3. The lock is ready-for-use with the new combination code.

MASTER KEY DECODE

Used to determine current lock combination.

1. Insert the Master Key into the operation knob and turn clockwise until the arrow on the operation knob is in the 12-o'clock position and the indicator is green.
2. Turn all (4) dials until it stops.
3. Turn the Master Key counterclockwise until the position indicator is green and remove master key.
4. The current 4-digit code shown is the current combination code, and the lock should now open without the key.

SALSBURY INDUSTRIES

18300 Central Avenue, Carson, CA 90746-4008
Phone: 1-800-562-5377 Int'l Phone: 323-846-6700
Fax: 1-800-562-5399 Int'l Fax: 323-846-6800
www.lockers.com engineering@lockers.com